

Flexible Motorized Roller Conveyor - 'O' Belt (Light Duty Dia 40mm)

Technical Specification:

Brand Name	: AIROLL
Model No	: FMRCL
Load Capacity	: 80 Kg per Linear Meter
Type	: Flexible Motorized Roller Conveyor – Driven By 'O' Belt
Roller Type	: AIROLL Make Dia 40mm Grooved Rollers - Zinc Plated
Roller Max. Open Pitch	: 125mm
Belt	: Rollers are driven from medium duty polyurethane Endless drive belts - AIROLL Make
Motor Power	: 90w per Meter
Conveyor Speed	: 30 / 45 Meter/Minute
Conveyor Widths	: 600mm, 800mm
Conveyor Height	: 700 – 1000 or 800 - 1200mm
Leg Support	: Telescopic Leg Supports - MS Powder Coated Light Grey RAL 7035
Castors Wheel	: 4" Swivel Wheels with Brakes
Links	: Medium duty Zinc Plated ribbed side links with better impact bearing.
Accessories	: Start/Stop and Emergency stop on front and end of the Conveyor Controlled by one independent electric box, loading and unloading, two-way operation End Stop Plate or End Stop Roller Pull Handle fitted both ends
Optional Accessories	: Optional Skate Wheel Side Guide Drop down End stop Plate and Drop-Down End Stop Roller Connecting Hooks to connect additional conveyor or more units
Packing Details	: Plywood Pallet, Cardboard, Bubble Film

Model No	Unit	Close Length (mm)	Open Length (mm)	Standard Width (mm)	Adjustable Height (mm)	Load Capacity (Kg/Linear Meter)	Leg Sets Per Unit
FMRCL	3	1050	3000	600 800	700 – 1000 Or 800 – 1200	80	4
	3	1400	4000				4
	4	1750	5000				5
	5	2150	6250				6
	6	2550	7500				7
	7	3000	8750				8
	8	3400	10000				9
	9	3850	11250				10
	10	4250	12500				11
	11	4650	13750				12
	12	5100	15000				13

Safety Information:

Do not put hands on Scissor Links

Keep the casters breaks down while in use

Clean the conveyor regularly to maintain the life span.

Do not overload. Max. capacity 80kg per linear meter

Do not sit, stand or walk on top of the conveyor