

Flexible Motorized Roller Conveyor - 'O' Belt (Medium Duty Dia 50mm)

Technical Specification:

Brand Name	: AIROLL
Model No	: FMRCM
Load Capacity	: 180 Kg per Linear Meter
Type	: Flexible Motorized Roller Conveyor – Driven By 'O' Belt
Roller Type	: AIROLL Make Dia 50mm Grooved Rollers - Zinc Plated
Roller Max. Open Pitch	: 125mm
Belt	: Rollers are driven from heavy duty polyurethane Endless drive belts - AIROLL Make
Motor Power	: 90w per Meter
Conveyor Speed	: 30 / 45 Meter/Minute
Conveyor Widths	: 600mm, 750mm, 900mm
Conveyor Height	: 700 – 1000 or 800 - 1200mm
Leg Support	: Telescopic Leg Supports - MS Powder Coated Light Grey RAL 7035
Castors Wheel	: 4" Swivel Wheels with Brakes
Links	: Heavy duty Zinc Plated ribbed side links with better impact bearing.
Accessories	: Start/Stop and Emergency stop on front and end of the Conveyor Controlled by one independent electric box, loading and unloading, two-way operation End Stop Plate or End Stop Roller Pull Handle fitted both ends
Optional Accessories	: Optional Skate Wheel Side Guide Drop down End stop Plate and Drop-Down End Stop Roller Connecting Hooks to connect additional conveyor or more units
Packing Details	: Plywood Pallet, Cardboard, Bubble Film

Model No	Unit	Close Length (mm)	Open Length (mm)	Standard Width (mm)	Adjustable Height (mm)	Load Capacity (Kg/Linear Meter)	Leg Sets Per Unit
FMRCM	3	1350	3000	600 750 900	700 – 1000 Or 800 – 1200	180	4
	4	1950	4500				5
	5	2450	5600				6
	6	2900	6750				7
	7	3400	7875				8
	8	3850	9000				9
	9	4350	10125				10
	10	4850	11250				11
	11	5300	12375				12
	12	5800	13500				13

Safety Information:

Do not put hands on Scissor Links

Keep the casters breaks down while in use

Clean the conveyor regularly to maintain the life span.

Do not overload. Max. capacity 180kg per linear meter

Do not sit, stand or walk on top of the conveyor

